

## GMP 規格

規格 \ PUMP TYPE	<b>GMP / GML / GMH</b>	
	60Hz	50Hz
最大揚程 (TDH Max.)(M)	60	40
最大流量 (Capacity Max.)(L/min)	550	450
最高溫 (Temperature Max.)	150°C / 150°C / 280°C	
最低溫 (Temperature Min.)	-30°C / -80°C / -30°C	
最大比重 (Specific Gravity Max.)	2	
最大黏度 (Viscosity Max.)	330 cp	
設計壓力 (Design pressure)	10 kgf/cm <sup>2</sup>	
口徑(入/出) Bore (Suc/Dis)	25/20 <sup>A</sup> – 50/40 <sup>A</sup>	
Flange Rating	JIS 10K / ANSI150	
葉輪樣式 (Impeller Type)	Closed	
馬達型式 (Motor Type)	Horiaontal 2P , 4P 0.75kW – 5.5kW	
材質 (Casing)	SCS14 (SUS316)	
墊片 (Gasket)	PTFE / GRAPHITE / GRAPHITE	
軸承 (Bearing)	SSiC	
軸套 (Sleeve)	SSiC	
磁鐵 (Magnet)	R.earth Nd / R.earth Nd / SmCo	
泵樣式 (Models fo Pump)	7	
軸承樣式 (Type of Bearing)	1	