

GMSW 規格

| 規格 | PUMP TYPE | |
|---|--------------------------------------|------|
| | GMSW / GMLW / GMHW | |
| | 60Hz | 50Hz |
| 最大揚程 (TDH Max.)(M) | 90 | 65 |
| 最大流量 (Capacity Max.)(L/min) | 50 | 45 |
| 最高溫 (Temperature Max.) | 150°C / 150°C / 280°C | |
| 最低溫 (Temperature Min.) | -30°C / -80°C / -30°C | |
| 最大比重 (Specific Gravity Max.) | 1.1 | |
| 最大黏度 (Viscosity Max.) | 50 cp | |
| 設計壓力 (Design pressure) | 16 kgf/cm ² | |
| 口徑(入/出) Bore (Suc/Dis) Flange Rating | PT 1/2" – PT 1" | |
| 葉輪樣式 (Impeller Type) | Closed | |
| 馬達型式 (Motor Type) | Horiaontal 2P , 4P 0.75kW – 3.7kW | |
| 材質 (Casing) | SCS14 (SUS316) | |
| 墊片 (Gasket) | PTFE | |
| 軸承 (Bearing) | SSiC | |
| 軸套 (Sleeve) | SSiC | |
| 磁鐵 (Magnet) | R.earth Nd / R.earth Nd / SmCo | |
| 泵樣式 (Models fo Pump) | 3 | |
| 軸承樣式 (Type of Bearing) | 1 | |